

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 604 875 B1**

(12)

**EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**21.04.1999 Bulletin 1999/16**

(51) Int Cl.<sup>6</sup>: **G01N 21/89**

(21) Application number: **93120586.8**

(22) Date of filing: **21.12.1993**

(54) **Continuous two dimensional monitoring of thin webs of textile materials**

Kontinuierliche zweidimensionale Überwachung von dünnem Gewebe textilen Materials

Monitorage continu bidimensionnel de tissu textile mince

(84) Designated Contracting States:  
**BE CH DE ES FR GB IT LI PT**

• **Baldwin, Joseph C.**  
**Knoxville TN 37923 (US)**

(30) Priority: **31.12.1992 US 999114**

(74) Representative: **Ellenberger, Maurice**  
**Zellweger Luwa AG**  
**Wilstrasse 11**  
**8610 Uster (CH)**

(43) Date of publication of application:  
**06.07.1994 Bulletin 1994/27**

(73) Proprietor: **ZELLWEGER USTER, INC.**  
**Knoxville, TN 37950-1270 (US)**

(56) References cited:  
**EP-A- 0 331 039** **DE-A- 3 819 183**  
**GB-A- 1 411 254** **GB-A- 2 236 389**  
**GB-A- 2 239 946** **US-A- 4 124 300**  
**US-A- 4 170 419**

(72) Inventors:  
• **Shofner, Frederick M.**  
**Knoxville TN 37922 (US)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 0 604 875 B1**

## Descripti n

### FIELD OF THE INVENTION.

[0001] The present invention relates to methods and apparatus for the in-process, real-time measurement and control of entities in thin webs of textile materials. In the preferred embodiment, such entities include single fibers, single neps, and single trash particles in cotton and other fibrous materials. The thin webs are either intentionally formed from a sample of material acquired from the process or inherently found within certain processing machines. Measurement is by image analysis preferably based on charge-coupled device (CCD) cameras with extended spectral response.

[0002] To further define the field of this invention, means are provided for acquisition of in-process samples from continuously-operating textile manufacturing process machinery. Image analysis then enables spatial, spectral, and temporal pattern recognition or filtering (SSTF). SSTF in turn enables identification of individual entities in the thin webs.

### BACKGROUND OF THE INVENTION.

[0003] The presence of undesirable entities in textile materials such as neps and trash particles is a problem whose severity is generally increasing. Production and harvesting techniques of cotton, for example, demand more aggressive cleaning action at the gin or in the early stages of processing in the textile mill. These actions remove foreign matter or trash but in many cases break the trash into smaller particles and leave some of it in the fibrous mass. This makes it more difficult to remove in later stages. Worse, this increasingly aggressive cleaning action generally increases the level of nep formation. It is therefore increasingly important to monitor the levels of these undesirable entities on a continuous basis in the gin or mill in order to optimally control them.

[0004] In most production environments it is completely impossible to monitor 100% of the process throughput and samples of in-process material must be acquired for measurement. In most textile processing machines the fiber samples conveniently available for sampling are in tuft form. New means are therefore needed to acquire a representative sample and prepare it into thin web format for image analysis measurement. There are notable exceptions where judicious application of recently-developed image analysis technology enable 100% monitoring of the process throughput. A good example, as will be disclosed below in a preferred embodiment, is monitoring the thin web of a carding machine. Prior art methods and apparatus result in overwhelmingly expensive or otherwise impractical applications of image analysis. Our invention overcomes the difficulties.

[0005] A further example is disclosed in GB 2 236 389 referring to an apparatus for detecting undesirable par-

ticles in textile fibre material. The textile fibre material is scanned by a camera and signals produced by said camera are processed digitally in a processing device. Processing comprises classifying registered undesirable particles on the basis of characteristics such as type, size, shape and counting and classifying the particles. A disadvantage of the known apparatus appears to be that whilst undesirable particles may be identified because they have parameters such as size, material, reflection properties and so on, which are different with respect to the fibre material in which they are embedded, if the used sensor does not distinguish undesirable particles according to one of these parameters, then, such particles may remain hidden in the textile fibre material.

[0006] GB 2 239 946 discloses a system for the detection of surface defects on band-like running material of paper, metal or textile. The surface is inspected by a camera and the position and the severity of defects on the surface are marked on a chart or on a surface image in order to be judged afterwards. This system shows the locations of defects and the severity of the defects based on a very simple discriminating procedure. A profound analysis of defects by means of digital signal processing appears not to be possible therewith.

[0007] GB 1 411 254 discloses an apparatus for detecting neps in a sliver of textile raw material. The apparatus comprises means for spreading the sliver into a thin web, a scanning device focused on the web and a counter for counting and for registering any change in the amount of light directed on the scanning device. In this apparatus neps in the web change the amount of light sensed by the scanning device and therefore neps are counted in the counter. This apparatus seems only able to detect neps or the like of a certain dimension. The apparatus appears to be unable to detect other undesirable elements in the web or to distinguish between elements having different characteristics.

[0008] US 4,170,419 discloses an optical web inspection system for detecting imperfections in a web. A plurality of sensor means are mounted above an inspection area and generate electrical output signals representing the intensity of the reflected radiation. The system further includes means for periodically summing the electrical output signals from the sensors to generate a summation signal. For determining an imperfection, single output signals are compared to the summation signal. The system is designed to report typically six types of defects which are present in a fabric web. Such types include warp, line, fill defects and so on.

### SUMMARY OF THE INVENTION

[0009] The invention as defined in claim 1 solves the problem encountered in the prior art.

[0010] With the present invention, on-line monitoring is provided for controlling the quality of card web. Undesirable entities are found in preferably 100% of the thin

card web, identified as to the severity of their impact upon subsequent processes or ultimately on sale price of the textile product derived therefrom, and then prioritized control action is taken to remove or exclude these entities from the web. These web-cleaning provisions are identified by the acronym "FIX".

[0011] In accordance with a preferred embodiment of the present invention, an apparatus is provided for monitoring a web of textile materials. The web may be monitored while it is being processed by textile processing machinery, or it may be formed separately from the textile processing machinery. The web includes a plurality of entities, such as fibers and trash. An imaging unit receives electromagnetic radiation from the web and produces image signals in response thereto. The image signals correspond to images of the web including the entities, and the web is in motion relative to the imaging unit. The imaging unit repetitively scans at least one stripe across the web in a direction substantially perpendicular to the direction of the relative motion of the web. A computer receives the image signals from the imaging units and produces digital data corresponding thereto. The computer analyzes the digital data and finds entities of interest in the web based on the analysis of such data. The computer further determines parameters of the found entities of interest and produces output signals indicating parameters of the entities of interest in the web.

[0012] In accordance with another preferred embodiment of the present invention, the imaging unit and computer further include distinguishing apparatus, such as a spectral grating or prism, for producing a plurality of optical images of the same portion of the web from the received electromagnetic radiation, where each of the optical images is distinguished from the others by the spectral content of the images. The computer produces a plurality of digital data representations corresponding to the plurality of optical images and analyzes the digital data to find images of entities of interest. The computer also determines the spectral content of the received electromagnetic radiation produced by the entity of interest based on the analysis of the plurality of digital data representations.

[0013] In accordance with another preferred embodiment of the present invention, the imaging unit further includes apparatus for producing a plurality of time separated images of the same portion of the web. In the preferred embodiment, a mask is disposed for receiving electromagnetic radiation from the web, for blocking portions of the electromagnetic radiation and for transmitting at least first and second spatially separated portions of the electromagnetic radiation. Imaging optics focus images of the first and second spatially separated portions of the electromagnetic radiation onto an array of detectors which produce image signals corresponding to the first and second spatially separated portions of the electromagnetic radiation.

[0014] In accordance with another preferred embodi-

ment of the present invention, the imaging unit produces at least first and second time separated images of the same portion of the web. The first time separated image is produced while the web is illuminated by a first illuminating condition, and the second time separated image is produced while the web undergoes a second illuminating condition which is different than the first illuminating condition. In one embodiment, the first illuminating condition is illumination of the front side of the web and the second illuminating condition is illumination of the back side of the web. The computer also classifies entities according to the apparent size of the entity, the apparent shape of the entity and the apparent color of the entity.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The present invention may best be understood by reference to the following Detailed Description of preferred embodiments when considered in conjunction with the drawings in which:

FIG. 1 is a somewhat diagrammatical cross-sectional view of tufts of fibers being transported pneumatically within a duct and showing a sampler in a wall of the duct;

FIG. 2 is an illustration similar to FIG. 1 showing a sampler in operation removing samples of fiber from the duct;

FIG. 3 is a somewhat diagrammatical drawing further illustrating the operation of the sampler and showing the sampler delivering fibers to a cylinder; FIG. 4 is a drawing showing the sampler delivering fiber samples to a cylinder which, in turn, delivers the sample to a glass plate;

FIG. 5 illustrates another embodiment of the present invention in which textile fibers are processed by a fiber individualizer, transported through an individual fiber monitor, and deposited on a cylindrical screen for further monitoring;

FIG. 6 is a cross-sectional view illustrating an implementation of the present invention in conjunction with a web on a doffer cylinder and/or a web as it leaves the doff rolls of a textile machine;

FIG. 8 shows a block diagram of an optical imaging system including two CCD cameras and front and back illumination of a web;

FIG. 9 is more detailed schematic diagram of the optical imaging system of FIG. 8;

FIG. 10 is detailed view of a mask used in the optical imaging system of FIG. 8;

FIG. 11 is a schematic diagram illustrating how the CCD camera is read into memory and into an image buffer;

FIG. 12 illustrates four books of memory into which images from the CCD are stored;

FIG. 13 illustrates an alternate system for reading the CCD camera and storing images in memory;

FIG. 14 is an overall block diagram of the processing system used to process the images produced by the optical imaging system;

FIG. 15 is a graphical illustration of two images in the image buffer;

FIGS. 16A and 16C represent possible geometric shapes of entities and FIGS 16B and 16D represent feature signatures of the entities shown in FIGS. 16A and 16C, respectively, where the signatures are generated by rotating a radius about the centroid of the geometric shape and graphing the length of the radius against its angular position;

FIGS 17A and 17B constitute a flow chart illustrating the operation of a computer program illustrating one method for using the optical system of the present invention for distinguishing between different entities in a textile web;

FIG. 18 shows an end cross-sectional view of a preferred excluder (ejector) of the present invention;

FIG. 19 shows a cross-sectional view of the excluder taken through section lines 19-19 shown in FIG. 18;

FIGS. 20 and 21 are enlarged views of the exclusions of 350 corresponding to FIGS. 18 and 19, respectively; and

FIG. 22 is a cross-sectional view illustrating an ejector system of the present invention implemented in conjunction with a clothed cylinder such as a doffer cylinder.

#### DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

##### WEB FORMING SAMPLER

[0016] FIG. 1 illustrates tufts of fiber 10 being transported pneumatically within a duct 11 in a direction indicated by arrow 13. On one side of the duct there is placed a perforated wall 12 in combination with a solid cover plate 14 to seal against the perforated wall and against the solid sides of the duct 11. This cover plate 14 overcomes pressure differentials between the inside and outside of the duct 11. Sampler plate 18, shown in stowed position in FIG. 1, is mounted on a drive mechanism 17, such as a hydraulic motor and control system, and is rotated about an axis 19 upon command from a control signal on line 21 into the flow, thus capturing tufts 10 which are impacted upon it. In the course of rotating counter-clockwise into the flow, impacted tufts 10 of suitable amount are collected and ultimately moved into a closed position by the rotary motion of the plate 18, as shown in FIG. 2. After plate 18 moves to the closed position shown in FIG. 2, the sealing plate 14 is removed by a suitable mechanical mechanism 23, such as a hydraulic piston and cylinder and control system, to expose the perforated wall 12, when appropriate control signals are applied through control lines 25.

[0017] FIG. 2 illustrates that the sampling plate 18 has

come to sampling position over the perforated plate 12. The sealing plate 14 has been retracted since the combined action of the fiber sample 20 on the perforated plate 12 and the sealing action of the sampling plate can withstand the pressure differential between the inside and outside of the duct 11.

[0018] As a result of this action, a fiber sample 20 is presented through the perforated plate holes 27 for sampling by a needle sampler 32.

[0019] In the right-hand side of the lower part of FIG. 2 there is shown, in broken line format, a needle sampler 32 with the locking/feed roll 34 in the retracted or open position. The needle sampler 32 (broken line) is just beginning its right to left motion. The row of needles 33, whose width into the paper is about 2 to 4 inches, move in close proximity to the perforated plate 12 and thereby acquires samples of entities 20 from the perforated holes 27 until the sampler 32 has been loaded and moved fully to the left. At this point the needle sampler 32 locking/feed roll 34 is closed, as shown in solid lines in the lower left side of FIG. 2, and the sample loading step has been completed. In this figure the roll 34 is intended to represent a conventional locking feed roll that rotates around its center axis and/or moves linearly in response to rotate and/or translate control signals.

[0020] The sampler 32 is carried by a suitable mechanism for translating it horizontally and rotating it downwardly. Preferably, the sampler 32 is fixedly mounted on an arm extending from hydraulic motor. A carriage is mounted on a linear chain drive and rails, and the carriage carries the motor through horizontal motion on the rails. A motor and motor control system under control of signals on lines 39 provide motive force to the chain drive and rails to drive the carriage and motor to thereby move the sampler 32 between the positions indicated by solid line sampler 32 and the broken line sampler 32. In addition, under control from signals on line, the motor selectively rotates the sampler in the direction indicated by arc.

[0021] As shown in FIG. 3 the needle sampler 32 has been rotated and translated away from the sampling position which is adjacent to the perforated plate 12. The sealing plate 14 is moved back into a closed position as shown in Figure 1 and the sampling plate 18 is rotated clockwise back into its stow position. The fibers which were captured on sampling plate 18 are blown away by compressed air and re-injected into the pneumatic conveying air in duct 16. FIG. 3 further illustrates that the needle sampler has been rotated into registration with presentation cylinder 40. Cylinder 40, which preferably includes pins 42 and perforations 44 on its surface, combs and aligns the fibers and serves as a presentation device for the thin web of fibers and other entities deposited thereupon. (The thin web is not shown.) Fibers are uniformly released from the pins 33 by rotating the locking/feed roll 34 in the fiber sampler 32 in concert with rotation of the thin web presentation cylinder 40 so that fibers are uniformly deposited onto the cylinder 40.

A plenum 43 and suction 45 on the plenum provide a suction through perforations 44 to assist the deposition of fibers from sampler 32 onto cylinder 40. The first objective of this transfer step is to transfer 100% of the fiber sample, including all entities in the sample such as neps or trash, without substantial modification. The second objective is forming the sample into the thin web format desired for presentation to the image analysis system 50. Preferably approximately 1 gram of sample is transferred from each needle sample 32 to the presentation cylinder 40. This quantity is associated with a needle sampler 32 width of approximately 4 inches.

**[0022]** The presentation cylinder 40 presents a thin web of entities for examination by image analysis means 50. In the embodiment of FIG. 3, fine pins 42 and perforations 44 on cylinder 40 are used to assure uniform removal and loading as well as to assure some combing and separation actions of the sample as it is removed from the needles 33. The image analysis means 50 thus examine a thin web which has been deposited in a preferred manner. Consideration is given to uniformity and orientation of fibrous entities in the material sample as will be fully disclosed hereinafter.

**[0023]** Before explaining the image analysis or control dimensions of this invention, completion of the sampling cycle is explained. Upon completion of the image analysis measurement by means 50, the brush 52 is moved to the right as indicated by arrows 53 such that the bristles 54 engage the pins 42. The brush 52 and the presentation cylinder 40 are rotated as shown by arrows 55 and 57 whereupon the fibers, neps, trash, and other entities are removed from the presentation cylinder 40 by the combined action by the brush 52 and compressed air 56 applied through the perforated holes 44. A coaxial adductor 58 is used to supply suction through conduit 59 with which to drive airflow from the brush 52 and presentation cylinder 40 region back into the pneumatic conveying process duct 11. Upon completion of this action, slide valve 60 closes. The system is now prepared for another measurement sequence. In the above description, mechanical movements and control are accomplished by conventional means and preferably the entire operation is under control of a conventional microprocessor based controller or a computer, such as the computer system 144 of Figure 8, but each step may be manually controlled, if desired.

**[0024]** FIG. 4 reveals another embodiment utilizing substantially the same image analyzer measurement means 50. A thin web 62 is formed for presentation to the image analysis system 50. In this case the sample is acquired by needle sampler 32 and spread on the presentation cylinder 40 as before but in this case the thin web 62 is brushed off onto a glass plate 64 whose length is slightly greater than the circumference of the preparation cylinder 40. The plate 64 is mounted for left and right linear motion as indicated by arrows 65 and is driven by drive rolls 67. In this manner the density, orientation and other preparation and presentation fea-

tures and effects on the sample by the cylinder 40 are retained but a preferred viewing environment 66 is provided. In this environment front lighting 68, and back lighting 70 may be used together or separately for preferred illumination. Background contrast and other elements are represented by the motor driven element carrier 72. The carrier 72 preferably provides a black background, but it also may represent white or other colors, a mirror surface, or no element at all, for the back lighting mode. A wide variety of backgrounds with front illumination could be chosen to enhance contrast or resolution or, in general, the ability to recognize entity patterns.

**[0025]** Upon completion of measurement the thin web sample 62 moves with the glass plate 64 under guide roll 76 and is removed by clean compressed air from purge source 77 and carried out by an air sweep 78 driven by coaxial adductor 80. The tested material is thus returned to the process as in FIG. 3. Cleaner wheel 75 removes residue and prepares the plate 64 for the next test.

**[0026]** FIG. 5 shows a fiber individualizing apparatus 102 supplying individual fibers and entities through a conduit to a sensing station 82 that in turn supplies the entities and fibers to a viewing station 88. \*\* The sample is individualized by apparatus 102. The individualized entities 103, after passing through electro-optical sensing station 82 (M3) are deposited on a rotating perforated drum 84. The deposition is aided by collection of the transport air by suction 86. At station 88 the image analysis system 50 is shown in similar function as in Figures 3 and 4. In this embodiment the sample has been conditioned with environmentally controlled gas 90 introduced at plenum 91 and discharged into a collection plenum 92 that is evacuated by suction 93. Also, the sample can be further conditioned by environmentally controlled air 94 which is similarly collected by plenum 96 and suction 97.

**[0027]** It is evident that the peripheral speed of perforated cylinder 84 can be adjusted in combination with the sample 100 feed rate into the fiber individualizer 102 so that essentially individual entities are presented for inspection both by the electro-optical sensor 82 and by the image analysis system 50. Slower speeds of the presentation cylinder 84 enable multiple entities to be deposited and inspected by the image analysis system 50 at station 88. It can be appreciated that a time stamping concept may be applied between the signals from the electro-optical light scattering sensor 82 and the image analysis system 50 at station 88. That is, there is a fixed time delay between when the sample 100 is sensed at station 82 and at station 88. Thus, the measurements from stations 82 and 88 may be time correlated.

**[0028]** FIG. 6 reveals a most important embodiment for on-line process monitoring wherein image analysis means 50 inspect the thin web on a doffer cylinder 110 of a carding machine 112. Alternatively, image analysis means 50 inspect the web 120 as it exits the doff or

crush rolls 122 and before it proceeds through a trumpet 125 and becomes a sliver 126. It will be readily understood that the entities, in terms of orientation and density are essentially the same on the doffing cylinder 110 as in the web 120. It will also be appreciated that the relative advantages of inspecting the web in "free" space 124, where front lighting and back lighting are much more readily achieved, is preferable for the highest contrast and resolution. However, in some cases it is not feasible to measure the web at space 124 as indicated in FIG. 6. Further, in other cases the discrimination abilities of the image analysis system 50 are entirely adequate when examining the thin web as it is transported by the teeth on the doffer cylinder 110.

**[0029]** FIGS. 3, 4, 5, and 6 thus disclose means by which thin webs may be formed from samples of textile material for the preferred examination by image analysis means. The samples may be automatically acquired from an operating process, may be part of a test sample for a laboratory quality control instruments, or may be inherently found already as thin webs in carding machines or the like. All may be advantageously examined with our preferred image analysis means 50. We now turn to the image analysis subject and disclose the concept of spatial, spectral and temporal pattern recognition or filtering, SSTF.

#### IMAGE ACQUISITION SYSTEM

**[0030]** Referring now to FIG. 8, there is shown an overview of the optical imaging system 129 which includes first and second optical imaging units 130 and 132, which include CCD cameras. Each of the imaging units 130 and 132 is positioned to view at least a 0.5 meter wide section of a web 134 which is preferably a web of non-woven textile fibers such as cotton. Preferably, the imaging units 130 and 132 are positioned to view approximately one-half of the web with an overlap 135 of approximately 0.01 meter. The purpose of two imaging units 130 and 132 is to provide 100% optical viewing of the web, but reduce the data rate by approximately one-half. That is, by analyzing the data from each optical unit 130 or 132 separately, the data rate is approximately one-half that which would be required if a single unit was viewing the entire web and the single camera was obtaining the same resolution as two imaging units.

**[0031]** The moving web 134 is illuminated by broad band radiation sources 136 and 138 which provide both visible and non-visible light including infrared. Source 136 illuminates the front of web 134 and source 138 illuminates the opposite side, the back side of web 134. With this illumination arrangement, the type of illumination impinging on the web 34 can be varied to provide information as to the amount of light transmitted through the web 134 from its back side or reflected from its front side or both.

**[0032]** The imaging units 130 and 132 and the illumi-

nation sources 136 and 138 are connected through data acquisition and control units 140 and 142 to an image processing and storage computer system 144. The optical imaging units 130 and 132 produce image signals that are transmitted through the units 140 and 142 to the system 144 for processing, and the computer system 144 also issues control commands through the units 140 and 142 to the illumination sources 136 and 138 and, thereby, controls the intensity and duration of the illumination on the web 134. The system 144 also includes an information link 146 that provides information and control to an excluder system that is hereinafter described.

#### OPERATION OF THE IMAGE ACQUISITION SYSTEM

**[0033]** The detailed operation of each of the optical imaging units 130 and 132 is best understood by reference to FIGS. 8 and 9. Referring to FIG. 8, there is shown a more detailed view of the optical imaging system 129 illustrating the operation of one imaging unit 130, it being understood that unit 132 functions in like manner. Referring to FIGS. 8 and 9, the optical unit 130 is configured to simultaneously view four stripes 150 across the web 134 that are labeled 1 - 4 on FIGS. 7 and 8. In the preferred embodiment, each of the stripes 150 has a width of 0.5 millimeters and extends in a traverse direction perpendicularly across the web 134 for a distance of approximately 0.510 meters. Since two optical imaging units 130 and 132 are used to view the entire web, the stripes 150 may be thought of actually extending continuously across the web. The four stripes 150 numbered 1-4 are separated each from the other by a distance of precisely 4.0 millimeters in a direction parallel to the direction in which the web 134 moves. Thus, the spacing, edge to edge, between the four stripes 150 is 3.5 millimeters.

**[0034]** The optical imaging system 129 includes a pair of lenses 153 and 154 and a spatial mask 156. The purpose of the lenses 153 and 154 is to focus an image of the web 134 unto a CCD camera and grating assembly 158 after reflection from mirror 160. The function of the spatial mask 156 is to restrict the view of the CCD and grating assembly 158 to the four stripes 150. Since the web 134 is moving in the direction indicated by arrow 160, it will be appreciated that the CCD and grating assembly 158 is viewing the web four separate times. That is, all of the web 134 will pass through each of the four stripes 150. Therefore, that portion of the web 134 that is first viewed in the first of the stripes 150 will be viewed a second time in the second stripe 150, a third time in the third stripe 150, and a fourth time in the fourth stripe 150. As described in greater detail hereinafter, this redundancy is provided for the purpose of increasing accuracy and/or increasing the amount of information obtained.

**[0035]** The signal from the CCD and grating assembly 158 is transmitted to readout electronics 162 which is a

part of the acquisition and control unit 140. The readout electronics 162 provides an output to an image processor 164 whose output is applied to a display and storage unit 166, both of which are part of the image processing and storage computer system 144.

[0036] The speed of the web 134 is constantly monitored by a speed detector, such as a rotary encoder 168, that provides speed information through readout electronics 162 to the computer system 144. This speed information is important so that the system can take advantage of the redundancy provided by the four stripes 150 and so that items of interest, such as trash, detected by the assembly 148 may be tracked as to position downstream in the web and excluded.

[0037] Referring now to FIG. 10, a detailed view of the mask 156 is shown. The mask 156 includes slits 170, 172, 173, and 174 that restrict the viewing angle of the CCD and grating assembly 158 to the four stripes 150. Thus, the slits 170, 172, 173, and 174 control the size and shape of the stripes 150. Since it is desired to provide stripes having a width of 0.5 millimeters, the width ( $d_x$ ) is determined by the product of the desired image width, 0.5 millimeters, and the magnification of the first optical element 152. The width of the mask  $d_y/2$  is determined by the product of the magnification of the lens 152 and the width of the web that is desired to be inspected (approximately 0.512 meters). Thus, for an optical element 152 with a focal length of 60 millimeters located 1 millimeter away, one would calculate as follows:

$$M = 63.8 \cdot 10^{-3}$$

$$\begin{aligned} d_x &= 32 \mu\text{m} \text{ and} \\ d_y &= 32\text{mm}. \end{aligned}$$

[0038] The mask 156 can be constructed of precision cut metal film or a chrome ruling on a glass substrate.

[0039] Referring now to FIG. 9, there is shown somewhat diagrammatic cross-sectional view of the CCD array and grating assembly 158. Light enters the assembly 158 through an electronic shutter 175 controlled by computer system 144 and first impinges upon a diffraction grating that is mounted by spacer blocks adjacent to a window in a housing. After passing through the shutter 175 and the diffraction grating, the light passes through the window and impinges upon a CCD array that is mounted on the opposite side of the housing. The diffraction grating disperses the incoming light into eight spectral channels, and the grating is oriented so that dispersion occurs in a direction corresponding to the movement direction of the web. Thus, the dispersion occurs in a direction perpendicular to the slits 170, 172, 173 and 174 and perpendicular to the four stripes 150. The diffraction grating is designed and dimensioned so that it spreads eight spectral channels over an area of the CCD corresponding to 4 millimeters on the web (eight

stripes on the web). Thus, instead of forming one image of each of the stripes 150 on the array 184, the system focusses eight side-by-side images of each of the stripes 150 on the array 184. It will now be appreciated that the size of the four stripes 150 and the spacing between the stripes 150 was chosen to allow for precisely eight images of each stripe on the CCD array 184 without allowing any overlap. Since the diffraction grating separates the light into spectral channels, each of the stripe images formed on the array 184 will provide different color information for each of the stripes 150. This design leads to a simple, compact design for observing color information in the visible wavelengths using a CCD array 184 that measures only the intensity of the light striking it.

[0040] In the above description, particularly with reference to FIG. 8, optical imaging unit 130 has been described along with the acquisition and control unit 140. It will be appreciated that the optical imaging unit 132 and 142 are substantially identical to units 130 and 140, respectively, and FIG. will be understood to describe and represent both imaging units 130 and 132 and both acquisition and control units 140 and 142.

[0041] The operation of the system 129 shown in FIG. 8 may be better understood by reference to the electronic and digital processing that is illustrated in FIGS. 11-14. The CCD array 184 consists of 1024 by 32 image pixels 190 arranged so that the 32 pixel dimension lies parallel to the movement of the image of web 134 on the array 184, and the rows of 1024 pixels 190 are oriented to be perpendicular across the image of the web 134 appearing on the array 184. The array 184 is preferably read four pixels at a time by an A/D convertor 192 where the voltage sensed by each pixel 190 is converted to a digital number which is output through the DEMUX 194 to digital memory 196. The memory is read by an averaging and total intensity accumulator 198 and its output is applied to an image buffer 200. The function of the accumulator 198 is to average four rows of 1024 pixel output from the array 184 to produce each row of the image placed in the image buffer 200. The averaging process may best be understood by again referencing FIG. 8 and considering a single one-half millimeter segment of the web 134 as it passes across the stripes 150. Consider first that this hypothetical segment first appears over the first stripe 150. The electronic shutter 175 will expose the CCD 184 and this hypothetical segment of the web will be viewed for the first time. The segment will then move from the first stripe 150 to the second stripe 150. The image processor 144 receives speed information from the encoder 168 and causes the shutter 175 to open each time the web moves one-half millimeter. Thus, the hypothetical segment will be positioned over the second stripe 150 when the shutter 175 opens for the ninth time and the segment will be viewed for a second time by the CCD array 184. Likewise, on the seventeenth exposure of shutter 175, the segment will be over stripe 3; on the twenty-fifth exposure of shutter 175,

the hypothetical segment will be over stripe 4 and, thus, it will be viewed for the third and fourth times. From the above explanation, it will be appreciated that each segment of the web will have the same hypothetical journey as described above and will be viewed four times. Thus, by averaging the first, ninth, seventeenth and twenty-fifth viewing of each 0.5 mm segment, an average measurement for each segment is obtained.

[0042] Referring now to FIG. 12, the control of the memory 196 may be visualized. The memory 196 is divided into four books, books one through four, which are identified by characters 202, 204, 206 and 208. Referring to FIGS. 12 and 13, the acquisition of data is explained as follows. Upon the receipt of a correct position indication from the rotary encoder 168 (FIG. 8), the shutter 175 (FIG. 10) opens for approximately 0.0001 second to expose the CCD array 184. The process of image acquisition begins by reading the first 1024 pixel line of the CCD array 184, four pixels at a time, and storing it in the rightmost 1024 locations of the first row of the first page of the first book. The next 1024 pixel line is read from the array 184 and is stored in book one, page two, row one, because it represents the same spatial information as the first line, but at a different spectral wavelength. Each book contains eight pages and the first eight lines of the CCD array 184 are read into the first rows of the eight pages of book one. The next eight lines of the CCD array are stored in the second row of the eight pages of book one. The next eight lines of the CCD array 184 (lines 16-24) are stored in row three of pages 1-8 of book one, and the final eight lines of the CCD array 184 are stored in row four of the eight pages of book one.

[0043] The CCD has now been fully read, and it is cleared and the processor 144 waits until the encoder 168 indicates that the web 134 has moved forward 0.5 millimeters. At that point, the shutter 175 will expose again and create exposure number two. Exposure number two is stored in book one, rows 5-8, of pages 1-8 in the manner described above. Likewise, subsequent exposures are stored in book one until exposure eight is stored in rows 29-32 of pages 1-8 of book one. On the ninth exposure, book two is begun as indicated by character 204 in FIG. 12. Book two will contain exposures 9-16. Likewise, books three and four are created for storing exposures 17-24 and exposures 25-32, respectively. From the above discussion it will be appreciated that book one contains the oldest exposures and book four contains the most recent exposures.

[0044] It will further be appreciated that row one of each of the pages in book one should correspond to the same web segment image as row two of each of the pages of book two, as row three of each of the pages of book three, and as row four of each of the pages of book four. Thus, to produce row one of the first page in the image buffer 200, the accumulator 198 averages book one page one row one + book two page one row two + book three page one row three + book four page one

row four. The accumulator 198 produces row one of pages 2-8 in the image memory buffer from pages 2-8 of books 1-4 in the same manner as described above.

[0045] To produce row two of page one in the image buffer 200, the accumulator 198 uses data obtained from exposures 2, 10, 18, and 26. Row two of image buffer 200 is obtained by averaging book one page one row five + book two page one row six + book three page one row seven + book four page one row eight. Likewise, each succeeding exposure is used to create the first eight rows in the eight pages of the image buffer 200. As another example, to produce row eight of the image buffer 200, the accumulator 198 adds book one row twenty-nine + book two row thirty + book three row thirty-one + book four row thirty-two. After the eighth row of image buffer 200 has been calculated, books two, three and four are redesignated as books one, two and three, respectively. Then, a new book four is created using the next eight exposures from the CCD 184, and the next eight rows for each of the eight pages of the image buffer 200 are calculated in the same manner as the first eight rows were calculated. This process continues indefinitely so that the image buffer 200 is a scrolling image buffer and always contains sixteen rows of image information on all eight pages. From the above description, it will be appreciated that the image buffer always contains eight images, which have been referred to as "pages", of sixteen rows each of the web 134. Each of the eight images (pages) differs from the other in image buffer 200 based on frequency (color). That is, each image represents a particular spectral range. If the web is producing an image in that particular spectral range, then such image will appear on the page of image buffer 200 containing that particular spectral range.

[0046] The output of the image buffer 200 is further analyzed as described in greater detail hereafter following a description of an alternate embodiment shown in FIG. 13 in which the accumulator 198 has been divided into two accumulators 198A and 198B, and the image buffer 200 has been divided into two buffers 200A and 200B. It will be understood that FIG. 13 is symbolically representing these elements and it is not necessary to actually physically separate the accumulators or the image buffers, but it is helpful to the explanation of the operation to so separate them.

[0047] The embodiment shown in FIG. 13 illustrates another way to take advantage of the redundancy that is built into the system 129. It will be recalled that each segment of the web 134 is viewed or imaged four times by the CCD 184. In the embodiment described above, these four redundant images were averaged to produce a single image. However, in the embodiment shown in FIG. 13, the redundancy is used in a different way. To utilize this embodiment, the illumination of the web 138 is changed after every sixteen exposures. For example, during the first sixteen exposures, the light source 138 is turned on to illuminate the web 134 from the back side of the web so that only light which transmits through the



web is received by the detector 184. On the second sixteen exposures (exposure 17-32) source 138 is turned off and source 140 is turned on so that only light reflected from the web is received by the array 184. Thereafter, the sources 138 and 140 are alternately turned on and off every sixteen exposures so that the web 134 is illuminated only from one side at a time. The accumulator 198A produces the image buffer 200A in book form in the manner described above, except that accumulator 198A receives data only from the first set of sixteen exposures plus every odd set of sixteen exposures thereafter when the source 138 is on. The accumulator 198 produces the image books in buffer 200B based only on even sets of sixteen exposures when source 140 is on and source 138 is off. Thus, image buffer 200A contains a transmitted light image and buffer 200B contains a reflected light image. Each of these images is actually eight images contained on eight separate pages in the manner described previously.

[0048] Another method for operating accumulators 198A and 198B is to change to the illumination after every eight exposures so that source 138 is on during exposures 1-8 and exposures 17-24, while source 140 is on during exposures 9-16 and 25-32. In such case, the accumulator 198 would produce information for the image buffer 200A only from odd numbered sets of eight exposures, and 198 would produce data for image buffer 200B only from even numbered sets of eight exposures.

[0049] Since there is a quadruple redundancy provided by the system shown in FIG. 8, if desired, all true redundancy may be eliminated and the web 134 may be observed under four different light conditions as it passes stripes 150. For example, the mat could be exposed to four different light conditions such that a different type of illumination is present each time a segment of the mat passes beneath one of the stripes 150. For example, the mat 134 could be illuminated with the color red for the first eight exposures, the color green for the second eight exposures, the color yellow for the third eight exposures and the color blue for the fourth eight exposures. On the fifth set of eight exposures, the light conditions would be cycled again in the same order as before for each set of eight exposures. In this manner, each segment of the mat 134 will be exposed to four different light conditions as it passed through stripes 150, and different portions of the mat 134 will be exposed to the various light conditions at differing locations. For example, one portion of the mat may be exposed to red at stripe one, whereas another portion of the mat will be exposed to red at stripe two. However, all segments of the mat will be exposed to all four light conditions, just at different positions. In this embodiment, it would be preferred to use four accumulators, such as accumulators 198A and 198B, each accumulator being programmed to accept data only when a certain light condition is illuminating the mat 134. In such case, each accumulator would be responsive to data from every

fourth set of eight exposures.

[0050] By the examples given above, it is meant to illustrate that the optical system of FIG. 8 can be constructed with a desired amount of redundancy by changing the number of stripes 150. This redundancy can be used to reduce the signal to noise ratio by exposing the mat 134 identically as the mat passes under each of the stripes 150 and then averaging the results. Or one may use the redundancy to expose the mat to differing light conditions, such as different wavelengths or directions or type of light, and thereby acquire more information about the web 134.

[0051] Referring again to FIGS. 11 and 13, it will be recalled that the array 184 includes lines of 1024 pixels and each pixel observes a 0.5mm X 0.5mm area of the web 134. Since the overall width of the web 134 is 1 meter, the two optical imaging units 130 and 132 may be set to overlap anywhere from 0 to 24 pixels. In the preferred embodiment, the units 130 and 132 are set to overlap by 20 pixels or 0.01 meters and, thus, each camera also has a viewing angle that overhangs the web on the outer edges by a distance of 4 pixels or 2 millimeters. The overlapping regions of the optical imaging units 130 and 132 are used to align the units 130 and 132 so that they are viewing precisely the same portion of the web 134 in the overlap region. Thus, the overlap insures full viewing of the web 134 and it facilitates alignment of the units 130 and 132. Also, it will be appreciated that a single optical imaging unit may be substituted for the units 130 and 132 by either reducing the desired resolution or by using a higher resolution CCD array 184.

#### IDENTIFICATION OF ENTITIES

[0052] Referring now to FIG. 14 a block diagram of the display and storage system 166 is shown. In this figure, two image buffers 210 and 212 are shown and each of these buffers is identical to buffer 200 shown in FIG. 11. Thus, the buffers 210 and 212 each contain eight images in eight memory locations which may be regarded as pages. Each of the pages is a 16 by 1024 array of data. The data of the image buffers 210 and 212 are read into processing buffers 214 and 216, respectively. Two digital signal processors (DSP) 218 and 220 are provided for operating upon the data in buffers 214 and 216, and each of the two DSP processor 218 and 220 is under the control of a central processor 222. The processor 222 is also connected to a conventional terminal 224 and to a communication link 146.

[0053] The raw data stored in the processing buffers 214 and 216 represents a multiplicity of features of the web 134. The DSP's 218 and 220 and the central processor 222 are programmed to use the spectral and spatial information contained in the images to locate entities of interest and classify or identify them. For example, in the preferred embodiment, the system 166 is programmed to locate trash and neps in a non-woven web of fiber 134. Referring to FIG. 17A, the first step 230 in

the program is to assign each pixel in the processing buffers 214 and 216 a binary value, 1 or 0, depending on its intensity value. For present purposes, we define any pixel having a value 1 (on) to be a feature, and any pixel with a value of 0 (off) to be background. For image information that was received in the transmitted light mode, objects of interest attenuate light so the program assigns a value of 1 to any pixel that is less than 30% of the background values for all of the pixels. For image information that was obtained in the reflective light mode, we are interested in pixels that have a value that is 30% above the background value and they are assigned a value of 1 and the remaining pixels are assigned a value of 0. This assignment of a binary value is performed for all of the images in the eight pages of the buffers 214 and 216. By assigning the binary values in the manner described above, the same feature recognition techniques and sizing algorithms may be used to operate on images produced by either transmitted or reflected light.

**[0054]** As indicated by step 232 in the flow chart following the conversion to a binary image, the image buffer is screened by checking the upper pixel row for feature overlapping. This can be accomplished by checking each pixel surrounding an upper row of pixels. If all five of the adjacent pixels are value 1, then the feature is considered to be an overlap. The number of rows occupied by that feature is then determined and that number is provided to the control circuitry to advance the refresh time by that number of rows. In this manner, the image buffer refresh time is controlled so that the images provided to the processing buffers 214 and 216 do not overlap the edges. In an alternate embodiment, rather than control the refresh timing of the image buffers to avoid overlaps, the processor identifies features of interest that lie on the last row (trailing edge) of the buffers 214 and 216. These identified features on a boundary are saved in a separate memory represented by the DSP's 218 and 220. Then, when the processing buffers 214 and 216 are refreshed, the first row (leading edge) of each of the buffers 214 and 216 is analyzed to locate the remaining portion of the saved feature that overlapped the boundary between the two pages in buffers 214 and 216. In this manner, the DSP's 218 and 220 reconstruct a single feature (particle image) from two features that overlapped a boundary.

**[0055]** After overlaps have been identified and compensated for, features are identified at step 234. Features are defined as two adjacent pixels with a value of 1. Adjacency can be horizontal, vertical or diagonal, and the total size of the particle is calculated by counting all adjacent pixels. The boundaries of these features are then determined, such as by tracing techniques, high pass filtering or derivative calculations. Once the features have been located and the boundaries have been determined, the features are further identified as to shape. For example, shape is determined by approximating the boundary of a feature with a polygon using

well known merging and splitting techniques. This technique works well because we expect relatively simply geometric shapes for most trash in cotton fibers and are primarily interested in the aspect ratio of the feature. An alternate method for determining the shape of a feature is to define a one-dimensional signature of the particle boundary. In accordance with this method, the distance from the centroid of the feature to the boundary of the feature is recorded as a function of the angle of the centroid. In FIG. 16A, a circular feature is illustrated with its corresponding signature produced by rotating a centroid shown in FIG. 16B. Compare the signature shown in 18B to the signature produced by rotating a centroid through a rectangle such as shown in 16C to produce the signature shown in 16D. This method is particularly suited to recognizing particles with a high degree of radial symmetry. Another advantage of this approach is that the features can be represented in one dimension thereby saving storage space and processing time.

**[0056]** After the features have been located and information has been obtained as to their size and shape, as indicated by step 236, the features are classified beginning with features with unusual spectral characteristics. Cotton color ranges from white to a very faint yellow in appearance, and any material which exhibits strong spectral responses other than yellow or white must be regarded as composed of foreign material for removal. For example, a nep containing sugar will exhibit a strong spectral response in the near infrared spectrum. Thus, any feature that has a strong response in the near infrared spectrum should be tagged as foreign material and removed as hereinafter described. The step 238 in the flow chart indicates immediate identification of foreign material based on spectral characteristics of a feature.

**[0057]** Next, features are selected one at a time from the reflected light buffer as indicated at step 239. If the feature is greater than 4 millimeters in diameter in any direction, for this particular application, it is regarded as an unknown foreign particle because most particles of interest such as trash, neps and seed coat fragments are smaller than 4 millimeters. Next, the size of the same feature when illuminated with transmitted light and a ratio is calculated. That is the size of the particle as observed in transmitted light is divided by the size of the particle as observed in reflected light. Since cotton is rather translucent, especially in a thin web, cotton itself is primarily observed by reflected light, as opposed to transmitted light. In contrast, opaque contaminants such as trash, grass and bark are revealed with high contrast under transmitted illumination, because they block substantially all of the light. Conversely, tight entanglements and clumps of fibers known as neps are best revealed in reflected light. Seed coat fragments which consist of both a translucent fiber mass and an opaque seed coat core are determined by comparing the response for both transmitted and reflected illumination. As shown in the flow chart at step 244, if the aforementioned ratio is less than 0.1, the feature is evaluated for radial symmetry at

step 246. If the feature has radial symmetry, such as shown in Figures 16A AND 16B, as indicated at step 248, it is identified as a nep. Otherwise it is identified as a clump or tuft as indicated at step 250. Referring to step 246, if the ratio falls between 0.1 and 0.8, it is immediately identified as a seed coat fragment as indicated at step 252. Finally, if the ratio is greater than 0.8 the program analyzes the aspect ratio as indicated at step 254. If the aspect ratio is small, such as less than 2, the particle is identified as leaf trash as indicated by step 256. On the other hand, if the aspect ratio is large, such as greater than 4, the trash is classified as bark or grass as indicated by step 258. The identification and classification of particles in the cotton web, such as the web 134 shown in FIG. 8, is useful for making decisions concerning the processing of the cotton both upstream and downstream from the point at which the cotton is observed. For example, if a very trashy cotton web is observed, the operator may choose to begin with cleaner cotton or increase the cleaning efficiency of upstream machines. If a particular type of trash is observed, it may indicate a particular type of problem upstream. For example, if odd color conditions are observed, it may indicate that a portion of a dyed rag has been introduced into the cotton upstream, and this event could ruin a great amount of end product.

**[0058]** Likewise, the identification and classification of particles in a cotton web provides useful information for downstream processing. For example, sugary neps, which would be indicated by a strong image in the near infrared region, interfere significantly with processing machinery and degrade the end product. Thus, in downstream processing, the elimination of the sugary neps could receive a high priority. In some applications, small leafy trash may present no problem, while grass fragments would be of concern. In such case, the downstream processing would emphasize the elimination of the detected grass and, perhaps, ignore the leafy trash.

#### EXCLUSION OF ENTITIES

**[0059]** Having described the above apparatus and method for finding and identifying trash in a cotton web, excluding undesirable entities from the thin web is now discussed. By means of the apparatus and method described above, entities are found and then identified in a prioritized classification as worthy of exclusion. Figure 18 shows an end cross sectional view of a preferred excluder 300 using compressed air to exclude or clear undesirable entities from the thin web 344, and Figure 19 shows a cross sectional view taken through section lines 19-19 shown in Figure 18. Figures 20 and 21 are enlarged views of the exclusion zone 150 corresponding to Figures 18 and 19, respectively. In the end views, Figures 6, 18 and 20, the thin web 320 is seen to be transported through plates 330 and 332 which have a row of inlet nozzles 334 with rectangular apertures 335 whose widths are on the order of three millimeters and are

shown in Figure 20 as having a width D, 338. In the cross sectional view of Figure 19, the length of the rectangular apertures 335 is shown to be on the order of one centimeter, and the spacing 335 (S) between the apertures is also in the order of one centimeter. The web 320 has a width of approximately one meter or 40 inches, and the row of nozzles 334 extends perpendicularly across the web 320. A single tapered deceleration nozzle 336 having a width of on the order of three millimeters, which is shown in Figure 20, and a length of a meter is positioned beneath the row of nozzles 334 and receives blasts of air therefrom.

**[0060]** Referring to Figures 8, 20 and 21, the row of nozzles 334 is positioned a known distance downstream of the stripes 150 shown in Figure 8. Since the speed of the web is constantly reported to the computer system 144 by the rotary encoder 168, the computer 144 calculates the time required for any particular segment of the web to pass from, for example, the first one of the stripes 150 to the row of nozzles 334. When an undesirable entity is identified by system 144, its position (spatial coordinates) is determined with respect to the thin web 134 (320 in Figure 18), and the system 144 calculates the time required for the undesirable entity to reach the row of nozzles. It will be recalled that the CCD arrays 184 in the imaging units 130 and 132 were arranged to view 0.5 mm stripes across the web 134 (320) with each pixel viewing a 0.5 mm rectangle. Thus by counting pixels across the array to the image of the undesirable entity, the lateral position of the entity is determined. Based on the lateral position of the entity, the computer system 144 also determines which nozzle 334 will be above the entity when it arrives at the nozzles 334. At the appropriate time, when the entity arrives in the exclusion zone 350, a short burst of compressed air is applied to an appropriate one of a plurality of eductor feed pipes 355 by one of the fast acting solenoid valves 154. The computer system 144 applies control signals through control lines 353 to actuate one or more of the valves 353 and release compressed air through the feed pipes 355. Clean compressed air is supplied by pipe 352 to each of the feed pipes 355, and each of the feed pipes is positioned in the mouth 337 of one of the nozzles 334. The compressed air exiting the feed pipe 355 entrains a volumetric flow from a plenum 360 that surrounds the nozzle mouths 337 and defines a chamber that is preferably slightly pressurized, as by compressed air 339. The combined air flow from the feed pipes 355 and the plenum 360 forms a blast of air that strikes and ejects the entity 356 out of the thin web 320, through the decelerating nozzle 336, and into a waste pipe 358. The decelerating nozzle 136 is sized to cause a very slight positive initial pressure in the exclusion zone 350, thus pushing the surrounding components of the thin web 320 away from the exclusion zone 350 while at the same time blasting the undesired entity 356 into the waste collection pipe 358. After the initial positive pressure, when the compressed air from feed pipe 335 is turned off,

there is a short interval of negative pressure caused by the momentum of the moving air in the decelerating nozzle 336 which causes the components surrounding the exclusion region (a rectangle of about 1 cm X 3 mm) to move inwardly; this negative pressure interval is timed to close the exclusion hole in the web 320 but to not pull the web 344 into the waste collection pipe 158.

[0061] Air is continuously moving through waste collection pipe 358 to transport the undesirable entities out of the system. Waste collection pipe 358 and inlet plenum 360 are sized to not interfere with the independent operation of the exclusion nozzles 334 and 336, of which there are about one hundred for a web from typical card. Furthermore, the supply air pipe 360 is sufficiently large that the interaction of the short pulse of any one of the exclusion nozzles 334 does not materially affect any of the others, even when more than one of these nozzles 334 is operating simultaneously. The air entering supply pipe 360 is filtered and otherwise conditioned to accommodate the purposes of exclusion.

[0062] FIG. 22 shows a second type of compressed air excluder 400 suitable for removing entities from clothed cylinders, such as the doffer cylinder 110 of FIG. 6. A preferred location 402 for excluder 400 marked as "X" on FIGS. 6 and 22 is between the image analyzer system 50 and the crush rolls 122. Referring now to FIG. 22, the image analyzer system 50 Finds and Identifies an entity on the doffer cylinder 110 which is to be excluded, said pattern recognition, decisions and timing being handled by computer 144 in FIG. 8, and control signals on lines 146 which cause excluder controller 404 to energize fast-acting solenoid valve 406. This action supplies clean compressed air to plenum 408 and to blast air orifice 410. Simultaneously, (or separately, with another valve and with different timing, if desired) solenoid valve 406 supplies clean compressed air to coaxial eductor 420. Assuming that blast air flow 412 and eductor driven air flow 416 start simultaneously, it is clear that the combined actions of pressure-driven blast air flow 412 and suction driven eductor air flow 416 are to "push and pull" a small volume or "pulse" of air, moving at high, across doffer wire 422 in a direction that permits the entity 418 and a few associated fibers 419 to be lifted off wire 422 and pulled into collector pipe 424. Flow 414 is driven by entrainment with flow 412 and by suction associated with flow 416. To summarize, the excluder 400 action may be thought of as providing a short duration (milliseconds) rapidly moving (near Mach 1) volumetric pulse (10's of cubic centimeters) which sweeps the entities off the cylinder wire and excludes them from the web. The width and length of the excluder orifices is about 3 mm X 10 mm, like the excluder 300 of FIGS. 18-21, and there are also 100 of them across the one meter width of the web on the doffer cylinder 110.

[0063] Compressed air exclusion nozzles are illustrated in this preferred embodiment but other exclusion means may be used as functionally equivalent. Such means include mechanical punching, cutting, or hook-

ing, or the like. While it is preferred to use the system 148 to Find and Identify the features of interest, such as trash in a moving cotton web, it should be understood that other detection systems could be used in conjunction with the excluder. Likewise, other excluders or fiber processors could be used with the detection system described herein. The various embodiments described herein are intended as examples illustrating the present invention and it will be understood that the present invention is capable of numerous rearrangements, modifications and substitution of parts without departing from the scope of the invention as defined in the appended claims.

## Claims

1. Apparatus for monitoring entities in a web of textile material, comprising a source (68, 70, 136, 138) for illuminating the web with electromagnetic radiation (62, 134), an imaging unit (50, 130, 132) for receiving electromagnetic radiation from said web and producing image signals in response thereto, said image signals corresponding to images of said web including said entities, said web being in motion relative to said imaging unit, said imaging unit being arranged for repetitively scanning at least one stripe across the web in a direction substantially perpendicular to the direction of relative motion of said web, and processing means (144) for receiving said image signals from said imaging units, for producing digital data corresponding to the image signals received from said imaging unit, for analyzing the digital data, for finding entities of interest in said web based on the analysis of the digital data, for determining parameters of said found entities of interest and for producing output signals indicating parameters of entities of interest in said web, characterized in that said processing means further comprise distinguishing means (156, 158) for producing a plurality of optical images (150) of the same portion of the web from the received radiation, each of said optical images being distinguished one from the others by the spectral content of the images, and said processing means being arranged for producing a plurality of digital data representations corresponding to the plurality of optical images, for analyzing each of the digital data representations to find images of entities of interest, for determining the spectral content of the received radiation produced by the entity of interest based on the analysis of the plurality of digital data representations.
2. Apparatus according to claim 1, wherein said processing means further comprises means for identifying an entity of interest as an undesirable entity based on the spectral content of the entity.

3. Apparatus according to claim 1, wherein said distinguishing means comprises: a mask (156) disposed for receiving electromagnetic radiation from the web, for blocking portions of the electromagnetic radiation, and for transmitting at least first and second spatially separated portions (150) of the radiation; spectral separation means (186) for separating the spatially separated portions of radiation into at least first and second spatially and spectrally separated portions; an array of detectors (184) for producing the image signals corresponding to the first and second spatially and spectrally separated portions; imaging optics (153, 154) for directing and focusing the spatially separated portions of the radiation and for focusing images of the first and second spatially and spectrally separated portions onto said array of detectors as images of different portions of the web.
4. Apparatus according to claim 3, wherein said portions of radiation are in the form of stripes, each of said first and second spatially and spectrally separated stripes being composed of a plurality of side-by-side spectral rows having different spectral content; said mask comprises at least first and second slits (170, 172) for transmitting first and second spatially separated stripes of the radiation through said slits, said stripes of radiation corresponding to stripes on the web; and said processing means being arranged for receiving the image signals, for producing digital data based on the image signals, for storing data corresponding to each spatially and spectrally separated stripe in the same position of different memory locations and for storing data corresponding to different spectral rows in different memory locations.
5. Apparatus according to claim 4, wherein said processing means are arranged for producing digital data in the form of books of data in a memory, each book having a plurality of pages and each page having a plurality of rows of data, for storing data corresponding to each spatially and spectrally separated stripe on the same row of different pages and for storing data corresponding to different spectral rows on different pages.
6. Apparatus according to claim 4, wherein said processing means are arranged to produce first and second digital representations of the same image of the web based upon image signals corresponding to the first and second spatially separated stripes respectively.
7. Apparatus according to claim 6, wherein said processing means further comprises means for averaging the first and second digital representations of the same image to produce an average digital representation.
8. Apparatus according to claim 6, wherein said processing means further comprises means for comparing the first and second digital representations of the same image to produce a comparison output indicating characteristics of entities of the web.
9. Apparatus according to claim 6, wherein said source of illumination is arranged for providing first and second conditions of illumination on the web, and, for each portion of the web, producing a different condition of illumination when the web portion is positioned at the first stripe as compared to when the same web portion is positioned at the second stripe so that each web portion is viewed by the array under at least two different illumination conditions; means for storing said first and second digital representations in memory locations corresponding to illumination conditions so that said first and second digital representations correspond to the same image of the web under said first and second illumination conditions respectively.
10. Apparatus according to claim 9, further comprising means for comparing said first and second digital representations and for classifying entities of interest based upon the comparison.
11. Apparatus according to claim 9, wherein said source of illumination is arranged for illuminating one side of the web and reflecting radiation from the web toward the imaging unit to produce the first illumination condition, which is a reflected illumination condition, and for illuminating the other side of the web and transmitting radiation through the web to produce the second illumination condition which is a transmitted illumination condition; and wherein said processing means are arranged for comparing said first and second digital representations and for finding and classifying entities of interest based upon the comparison.
12. Apparatus according to claim 11, wherein said processing means are further arranged for determining first and second apparent sizes of an entity of interest based upon the first and second digital representations, respectively, and for determining that the entity of interest is composed of fibre when the first apparent size is greater than the second apparent size by a predetermined amount.
13. Apparatus according to claim 12, wherein said processing means are arranged for determining whether the first apparent size is within a predetermined range and identifying an entity of interest as corresponding to nep if the first apparent size is

within the predetermined range and the first apparent size is greater than the second apparent size by a predetermined amount.

14. Apparatus according to claim 1, wherein said processing means are arranged for determining the apparent shape of the entities of interest based on the analysis of the digital data and classifying the entities of interest as to type based at least in part on the apparent shape. 5
15. Apparatus according to claim 1, wherein said processing means are arranged for determining the apparent size of the entities of interest based on the analysis of the digital data and classifying the entities of interest as to type based at least in part on the apparent size. 10
16. Apparatus according to claim 1, wherein said processing means are arranged for determining the apparent colour of the entities of interest based on the analysis of the digital data and classifying the entities of interest as to type based at least in part on the apparent colour. 15
17. Apparatus according to claim 1, wherein said processing means are arranged for determining the position of the entities of interest based on the analysis of the digital data and producing output signals including information as to the entity position. 20
18. Apparatus according to claim 1, further comprising means for forming the web and presenting it for viewing to said imaging unit. 25

#### Patentansprüche

1. Vorrichtung zur Überwachung von Teilchen in einer Bahn aus textilem Material mit einer Quelle (68, 70, 136, 138) zur Beleuchtung der Bahn mit elektromagnetischer Strahlung (62, 134), mit einer Abblendeinheit (50, 130, 132), welche die elektromagnetische Strahlung von der Bahn empfängt und als Antwort darauf Bildsignale erzeugt, wobei diese Bildsignale Bilder der Bahn mit den Teilchen entsprechen, wobei die Bahn relativ zu der Abblendeinheit bewegt ist, die Abblendeinheit für wiederholtes Abtasten mindestens eines Streifens über der Bahn in einer im wesentlichen senkrechten Richtung zu der relativen Bewegung der Bahn angeordnet ist, und mit einem Rechner (144), der die Bildsignale von den Abblendeinheiten erhält um digitale Signale zu erzeugen, die den Bildsignalen aus den Abblendeinheiten entsprechen, zum Untersuchen der digitalen Daten, zum Auffinden von interessierenden Teilchen in der Bahn durch Untersuchung der digitalen Signale, zum Bestimmen von Parametern der ge- 40

fundenen interessierenden Teilchen und zum Erzeugen von Ausgangssignalen, die Parameter der interessierenden Teilchen in der Bahn angeben, dadurch gekennzeichnet, dass der Rechner weitere Mittel (156, 158) zur Unterscheidung aufweist, zur Erzeugung mehrerer optischer Bilder (150) desselben Abschnitts der Bahn aus der erhaltenen Strahlung, wobei jedes Bild sich von den anderen Bildern durch das Spektrum des Inhaltes unterscheidet, und wobei der Rechner zur Erzeugung einer Vielzahl von Darstellungen aus digitalen Daten ausgebildet ist, die den mehreren optischen Bildern entsprechen, um jede digitale Darstellung eines Bildes zu untersuchen, um Bilder von interessierenden Teilchen zu finden, und um den Inhalt des Spektrums der erhaltenen und vom interessierenden Teilchen erzeugten Strahlung ausgehend von der Untersuchung der mehreren digitalen Darstellungen zu bestimmen.

2. Vorrichtung nach Anspruch 1, wobei der Rechner weitere Mittel zur Bestimmung eines interessierenden Teilchens als unerwünschtes Teilchen, aus dem Inhalt des Spektrums des Teilchens, enthält. 25
3. Vorrichtung nach Anspruch 1, wobei die Mittel zur Unterscheidung eine Maske (156), die zum Empfang elektromagnetischer Strahlung aus der Bahn angeordnet ist, um Teile der elektromagnetischen Strahlung abzuschatten und um mindestens erste und zweite räumlich getrennte Teile (150) der Strahlung zu übertragen, Mittel (186) zur spektralen Trennung der räumlich getrennten Teile der Strahlung mindestens in erste und zweite räumlich und spektral getrennte Teile, eine Anordnung von Detektoren (184) die Bildsignale erzeugen, die den ersten und zweiten räumlich und spektral getrennten Teilen entsprechen, und abbildende Optiken (153, 154), die die räumlich getrennten Teile der Strahlung lenken und bündeln und Bilder der ersten und zweiten räumlich und spektral getrennten Teile auf die Anordnung der Detektoren als Bilder von verschiedenen Abschnitten der Bahn bündeln, aufweisen. 30
4. Vorrichtung nach Anspruch 3, wobei die Teile der Strahlung die Form von Streifen aufweisen, jeder der ersten und zweiten räumlich und spektral getrennten Streifen aus einer Mehrzahl von nebeneinanderliegenden spektralen Reihen mit unterschiedlichem Inhalt des Spektrums bestehen, die Maske mindestens erste und zweite Schlitze (170, 172) zur Übertragung erster und zweiter räumlich getrennter Streifen der Strahlung durch diese Schlitze aufweist, diese Streifen der Strahlung Streifen des Bandes entsprechen, und wobei der Rechner zum Empfang von Bildsignalen, zur Erzeugung von digitalen Signalen aus den Bildsignalen, zur Speiche- 35

- rung von Daten, die jedem räumlich und spektral  
 getrennten Streifen am gleichen Ort in verschiede-  
 nen Speicherplätzen entsprechen, und zum Spei-  
 chern von Daten, die verschiedenen spektralen  
 Reihen in verschiedenen Speicherplätzen entspre-  
 chen, ausgebildet ist.
5. Vorrichtung nach Anspruch 4, wobei der Rechner  
 zur Erzeugung von digitalen Daten in der Form von  
 Büchern in einem Speicher ausgebildet ist, jedes  
 Buch eine Mehrzahl Seiten und jede Seite eine  
 Mehrzahl Datenreihen aufweist, um Daten, die je-  
 dem räumlich und spektral getrennten Streifen ent-  
 sprechen, in derselben Reihe auf verschiedenen  
 Seiten zu speichern und um Daten, die verschiede-  
 nen spektralen Reihen entsprechen, auf verschiede-  
 nen Seiten zu speichern.
6. Vorrichtung nach Anspruch 4, wobei der Rechner  
 so ausgebildet ist, dass zuerst erste und zweite di-  
 gitale Darstellungen desselben Bildes der Bahn,  
 ausgehend von Bildsignalen, die ersten und zwei-  
 ten räumlich getrennten Streifen entsprechen, er-  
 zeugt werden.
7. Vorrichtung nach Anspruch 6, wobei der Rechner  
 weitere Mittel zur Mittelung der ersten und zweiten  
 digitalen Darstellung desselben Bildes aufweist, um  
 eine gemittelte digitale Darstellung zu erzeugen.
8. Vorrichtung nach Anspruch 6, wobei der Rechner  
 weitere Mittel zum Vergleichen der ersten und zwei-  
 ten digitalen Darstellung desselben Bildes aufweist,  
 um ein Vergleichssignal zu erzeugen, das Eigen-  
 schaften von Teilchen im Band angibt.
9. Vorrichtung nach Anspruch 6, wobei die Quelle zur  
 Beleuchtung so angeordnet ist, dass auf der Bahn  
 erste und zweite Beleuchtungsverhältnisse erzeugt  
 werden, und dass für jeden Abschnitt der Bahn ver-  
 schiedene Beleuchtungsverhältnisse vorliegen, je  
 nach dem der Abschnitt der Bahn unter dem ersten  
 Streifen oder unter dem zweiten Streifen liegt, so  
 dass jeder Abschnitt der Bahn von der Anordnung  
 unter mindestens zwei verschiedenen Beleuch-  
 tungsverhältnissen erfasst wird, mit Mitteln zum  
 Speichern dieser ersten und zweiten digitalen Dar-  
 stellungen in Speicherplätzen, die den Beleuch-  
 tungsverhältnissen zugeordnet sind, so dass die er-  
 ste und die zweite digitale Darstellung demselben  
 Bild der Bahn unter den ersten und zweiten Be-  
 leuchtungsverhältnissen entspricht.
10. Vorrichtung nach Anspruch 9, mit weiteren Mitteln  
 zum Vergleichen dieser ersten und zweiten digita-  
 len Darstellung und zum Klassieren von interessie-  
 renden Teilchen ausgehend von dem Vergleich.
11. Vorrichtung nach Anspruch 9, wobei die Quelle zur  
 Beleuchtung so angeordnet ist, dass die eine Seite  
 der Bahn beleuchtet wird und dass Strahlung von  
 der Bahn zur Abbildeinheit reflektiert wird, so dass  
 erste Beleuchtungsverhältnisse entstehen, die Re-  
 flexions-Beleuchtungsverhältnisse sind, und dass  
 die andere Seite der Bahn beleuchtet und die Strah-  
 lung durch die Bahn hindurch übertragen wird, so  
 dass zweite Beleuchtungsverhältnisse entstehen,  
 die Übertragungs-Beleuchtungsverhältnisse sind,  
 und wobei der Rechner so ausgebildet ist, dass er  
 diese erste und zweite digitale Darstellung verglei-  
 chen und durch diesen Vergleich interessierende  
 Teilchen finden und klassieren kann.
12. Vorrichtung nach Anspruch 11, wobei der Rechner  
 weiter so ausgebildet ist, dass er aus den ersten  
 oder zweiten digitalen Darstellungen erste und  
 zweite sichtbare Grössen eines interessierenden  
 Teilchens bestimmen kann und dass er bestimmen  
 kann, dass das interessierende Teilchen aus Fa-  
 sem besteht, wenn die erste sichtbare Grösse um  
 einen vorgegebenen Betrag grösser ist als die zwei-  
 te sichtbare Grösse.
13. Vorrichtung nach Anspruch 12, wobei der Rechner  
 so ausgebildet ist, dass er bestimmen kann, ob die  
 erste sichtbare Grösse innerhalb eines bestimmten  
 Bereiches liegt und das interessierende Teilchen  
 als Nisse identifizieren kann wenn die erste sicht-  
 bare Grösse innerhalb des vorbestimmten Berei-  
 ches liegt und die erste sichtbare Grösse um einen  
 bestimmten Betrag grösser ist als die zweite sicht-  
 bare Grösse.
14. Vorrichtung nach Anspruch 1, wobei der Rechner  
 so ausgebildet ist, dass er die sichtbare Form der  
 interessierenden Teilchen ausgehend von einer  
 Untersuchung der digitalen Daten bestimmen kann  
 und dass er die interessierenden Teilchen minde-  
 stens teilweise aus der sichtbaren Form gemäss ih-  
 rem Typ klassieren kann.
15. Vorrichtung nach Anspruch 1, wobei der Rechner  
 so ausgebildet ist, dass er die sichtbare Form der  
 interessierenden Teilchen ausgehend von einer  
 Untersuchung der digitalen Daten bestimmen kann  
 und dass er die interessierenden Teilchen minde-  
 stens teilweise aus der sichtbaren Grösse gemäss  
 ihrem Typ klassieren kann.
16. Vorrichtung nach Anspruch 1, wobei der Rechner  
 so ausgebildet ist, dass er die sichtbare Farbe der  
 interessierenden Teilchen ausgehend von einer  
 Untersuchung der digitalen Daten bestimmen kann  
 und dass er die interessierenden Teilchen minde-  
 stens teilweise aus der sichtbaren Farbe gemäss  
 ihrem Typ klassieren kann.

17. Vorrichtung nach Anspruch 1, wobei der Rechner so ausgebildet ist, dass er die sichtbare Lage der interessierenden Teilchen ausgehend von einer Untersuchung der digitalen Daten bestimmen kann und dass er Ausgangssignale ausgibt, die Angaben über die Lage der Teilchen enthalten.
18. Vorrichtung nach Anspruch 1, mit Mitteln zur Bildung der Bahn und zu deren Vorlage zur Erfassung durch die Abbildeinheit.

## Revendications

1. Appareil pour surveiller des entités dans une bande de matière textile, comprenant une source (68, 70, 136, 138) pour éclairer une bande avec un rayonnement électromagnétique (62, 134), une unité d'imagerie (50, 130, 132) pour recevoir le rayonnement électromagnétique de ladite bande et pour produire des signaux d'image en réponse à celui-ci, lesdits signaux d'image correspondant aux images de ladite bande incluant lesdites entités, ladite bande étant en mouvement relativement à ladite unité d'imagerie, ladite unité d'imagerie étant agencée pour balayer à répétition au moins une rayure à travers la bande, dans une direction sensiblement perpendiculaire à la direction du mouvement relatif de ladite bande, et un moyen de traitement (144) pour recevoir lesdits signaux d'image desdites unités d'imagerie, pour produire des données numériques correspondant aux signaux d'image reçus de ladite unité d'imagerie, pour analyser les données numériques, pour trouver des entités d'intérêt dans ladite bande basées sur l'analyse des données numériques, pour déterminer des paramètres desdites entités d'intérêt trouvées et pour produire des signaux de sortie indiquant des paramètres des entités d'intérêt dans ladite bande, caractérisé en ce que ledit moyen de traitement comprend en outre un moyen de distinction (156, 158) pour produire une pluralité d'images optiques (150) de la même partie de la bande du rayonnement reçu, chacune desdites images optiques se distinguant des autres par le contenu spectral des images, et ledit moyen de traitement étant agencé pour produire une pluralité de représentations de données numériques correspondant à la pluralité des images optiques, pour analyser chacune des représentations des données numériques pour trouver des images des entités d'intérêt, afin de déterminer le contenu spectral du rayonnement reçu produit par l'entité d'intérêt sur la base de l'analyse de la pluralité des représentations des données numériques.
2. Appareil selon la revendication 1, où ledit moyen de traitement comprend en outre un moyen pour identifier une entité d'intérêt comme une entité non re-

cherchée, sur la base du contenu spectral de l'entité.

3. Appareil selon la revendication 1, où ledit moyen de distinction comprend un masque (156) disposé pour recevoir un rayonnement électromagnétique de la bande, pour bloquer des parties du rayonnement électromagnétique et pour transmettre au moins des première et deuxième portions spatialement séparées (150) du rayonnement; un moyen de séparation spectral (186) pour séparer les portions spatialement séparées du rayonnement en au moins des première et deuxième portions séparées spatialement et spectralement; une rangée de détecteurs (184) pour produire les signaux d'image correspondant auxdites première et deuxième portions séparées spatialement et spectralement; des optiques d'imagerie (153, 154) pour diriger et focaliser les portions spatialement séparées du rayonnement et pour focaliser des images des première et deuxième portions séparées spatialement et spectralement sur ladite rangée de détecteurs, comme images de différentes portions de la bande.
4. Appareil selon la revendication 3, où lesdites portions de rayonnement se présentent sous la forme de rayures, chacune desdites première et deuxième rayures séparées spatialement et spectralement étant constituée d'une pluralité de rangées spectrales côte-à-côte d'un contenu spectral différent; ledit masque comprend au moins des première et deuxième fentes (170, 172) pour transmettre des première et deuxième rayures spatialement séparées du rayonnement à travers lesdites fentes, lesdites rayures de rayonnement correspondant aux rayures sur la bande; et ledit moyen de traitement étant agencé pour recevoir les signaux d'image, pour produire des données numériques sur la base des signaux d'image, pour stocker des données correspondant à chaque rayure séparée spatialement et spectralement dans la même position d'emplacements de mémoire différents, et pour stocker des données correspondant aux rangées spectrales différentes dans différents emplacements de mémoire.
5. Appareil selon la revendication 4, où ledit moyen de traitement est agencé pour produire des données numériques sous la forme de livres de données dans une mémoire, chaque livre ayant plusieurs pages et chaque page ayant plusieurs rangées de données, pour stocker des données correspondant à chaque rayure séparée spatialement et spectralement sur la même rangée de différentes pages, et pour stocker des données correspondant aux rangées spectrales différentes sur différentes pages.



6. Appareil selon la revendication 4, où ledit moyen de traitement est agencé pour produire des première et deuxième représentations numériques de la même image de la bande basée sur des signaux d'image correspondant aux première et deuxième rayures spatialement séparées, respectivement. 5
7. Appareil selon la revendication 6, où ledit moyen de traitement comprend en outre un moyen pour faire la moyenne des première et deuxième représentations numériques de la même image, pour produire une représentation numérique moyenne. 10
8. Appareil selon la revendication 6, où ledit moyen de traitement comprend en outre un moyen pour comparer les première et deuxième représentations numériques de la même image, pour produire une sortie de comparaison indiquant des caractéristiques des entités de la bande. 15
9. Appareil selon la revendication 6, où ladite source d'éclairage est agencée pour réaliser des premier et deuxième états d'éclairage sur la bande et, pour chaque portion de la bande, produire un état d'éclairage différencé lorsque la portion de bande est positionnée à la première rayure comparée au moment où la même portion de bande est positionnée à la deuxième rayure, de telle sorte que chaque portion de bande est observée par la rangée sous au moins deux états d'éclairage différents, un moyen pour stocker les première et deuxième représentations numériques dans des emplacements de mémoire correspondant aux états d'éclairage de façon que lesdites première et deuxième représentations numériques correspondent à la même image de la bande sous lesdites premières et deuxième conditions d'éclairage, respectivement. 20 25 30
10. Appareil selon la revendication 9, comprenant en outre un moyen pour comparer lesdites première et deuxième représentations numériques et pour classer les entités d'intérêt sur la base de la comparaison. 35 40
11. Appareil selon la revendication 9, où ladite source d'éclairage est agencée pour éclairer un côté de la bande et pour réfléchir le rayonnement de la bande vers l'unité d'imagerie pour produire le premier état d'éclairage, qui est un état d'éclairage réfléchi, et pour éclairer l'autre côté de la bande et transmettre le rayonnement à travers la bande pour produire le deuxième état d'éclairage, qui est un état d'éclairage transmis; et où ledit moyen de traitement est agencé pour comparer lesdites première et deuxième représentations numériques et pour trouver et classer les entités d'intérêt sur la base de la comparaison. 45 50 55
12. Appareil selon la revendication 11, où ledit moyen de traitement est agencé en outre pour déterminer des première et deuxième tailles apparentes d'une entité d'intérêt sur la base des première et deuxième représentations numériques, respectivement, et pour déterminer que l'entité d'intérêt est constituée de fibres lorsque la première taille apparente est plus grande que la deuxième taille apparente d'une valeur prédéterminée.
13. Appareil selon la revendication 12, où ledit moyen de traitement est agencé pour déterminer si la première taille apparente se situe dans une plage prédéterminée et pour identifier une entité d'intérêt comme correspondant à un nœud, si la première taille apparente se situe dans la plage prédéterminée et que la première taille apparente est plus grande que la deuxième taille apparente d'une valeur prédéterminée.
14. Appareil selon la revendication 1, où ledit moyen de traitement est agencé pour déterminer la forme apparente des entités d'intérêt sur la base de l'analyse des données numériques et pour classer les entités d'intérêt quant à leur type, basé au moins en partie sur la forme apparente.
15. Appareil selon la revendication 1, où ledit moyen de traitement est agencé pour déterminer la taille apparente des entités d'intérêt basée sur l'analyse des données numérique et pour classer les entités d'intérêt quant à leur type, basé au moins en partie sur la taille apparente.
16. Appareil selon la revendication 1, où ledit moyen de traitement est agencé pour déterminer la couleur apparente des entités d'intérêt, basée sur l'analyse des données numériques, et pour classer les entités d'intérêt quant à leur type, basé au moins en partie sur la couleur apparente.
17. Appareil selon la revendication 1, où ledit moyen de traitement est agencé pour déterminer la position des entités d'intérêt, basée sur l'analyse des données numériques, et pour produire des signaux de sortie incluant des informations se rapportant à la position de l'entité.
18. Appareil selon la revendication 1, comprenant en outre un moyen pour former la bande et pour la présenter, en vue de l'observation, à ladite unité d'imagerie.

Fig. 1





Fig. 2







Fig. 4



**Fig. 5**




Fig. 6




Fig. 8






Fig. 9







Fig. 10







**Fig. 13**




Fig. 14




Fig. 15




Fig. 16




Fig. 16A




Fig. 16C




Fig. 16B




Fig. 16D



Fig. 17A




Fig. 17B




Fig. 18




Fig. 19




Fig. 20





Fig. 21






Fig. 22